



date _____
 customer _____
 project _____
 quantity _____

SmartLedFlex® is a flexible linear lighting product for both indoor and outdoor (IP66) applications. It is perfect for architectural illumination that provides a high performance homogenous light to highlight the perimeters and outlines of buildings, bridges, etc.

SmartLedFlex® has 100 LEDs/m. SMD Nichia Side View enclosed in special flexible polymer material, which allow the product to be bent into different winding shapes and the product is protected against UV rays thanks to the silicone outer shell.

Available in a wide range of colors and two versions; square and round.

SMART LED FLEX Luminaire



Family	Type	Run length	Color temp / Wattage / Lumens	Driver	Input voltage
MC-7211		Advise on run length			
0	round monocolour	* Max 33' Run --->	70/2K7 2700K 2.93W 47lm/FT	N non dim	24 24VDC input 120/277V
1	square monocolour	* Max 33' Run --->	70/3K5 3500K 2.93W 68 lm/FT	A 0-10V	
2	round RGB	* Max 33' Run --->	70/5K2 5200K 2.93W 85 lm/FT	D DMX	
3	square RGB	* Max 33' Run --->	07 yellow 1.47W 29 lm/FT		
		* Max 33' Run --->	04 amber 1.47W 41 lm/FT		
		* Max 33' Run --->	03 red 1.47W 14 lm/FT		
		* Max 33' Run --->	09 blue 2.93W 6 lm/FT		
		* Max 33' Run --->	08 green 2.93W 29 lm/FT		
		** Max 26' Run --->	11 RGB 3.66W 38 lm/FT		



example...

Family	Type	Run Length	Color temp / Wattage / Lumens	Driver	Input voltage
MC-7211	0	?	70/3K5	A	24

* Priced based on 33 ft. run for colored white. Max 33 ft. run per driver.

** Priced based on 26 ft. run for RGB. Max 26 ft. run per driver.

