




date _____
 customer _____
 project _____
 quantity _____

PIANO-P Luminaire



Ceiling an pendant luminaire with direct-indirect lighting for balanced room ambience, light component: approx. direct 50% / indirect 50%, trooping function (communication system between luminaires for light and movement), outstanding ease of maintenance, housing made from aluminium and die-cast zinc, diffuser made from prismatic acrylic glass with side-emitting LEDs (diffuser is completely transparent when switched off), Y-wire-rope suspension 2-fold with height adjustment (length: 59.1in), transparent connecting cable (5-core, pre-fabricated), ceiling box made from ABS plastic in the same color as the luminaire, LED converter integrated.



Family	Wattage / Lumens / Length			Mounting		Color temp		Beam		Finish		Driver		CRI		Input voltage	
PIANO-P																	
10A	80W	>8380lm	55.1in	P	pendant	30	3000K	S	standard	S	silver	N	non dim	80	CRI80	120	120V input
10B	120W	>12570lm	76.8in			40	4000K			W	white	A	0-10V			277	277V input
10C	160W	>16760lm	101.3in									C	consult for options				



example...

Family	Wattage / Lumens / Length			Mounting		Color temp		Beam		Finish		Driver		CRI		Input voltage	
PIANO-P																	
	10A			P		30		S		S		A		80		120	

