


date	
customer	
project	
quantity	

LILI LED

Luminaire



High-class LED luminaire designed for direct or direct-indirect light emission, with round lamp housing in a flat design made of seamlessly welded, powder-coated extruded aluminum. Available in white or RAL color. Electrical connection through 3 or 5-pin transparent power supply cable and ceiling housing. Indirect light emission through separate LED boards. Indirect light emission from 10 to 25%, depending on the size of the luminaire and the power output. Direct light emission through a diffuser made of satined PMMA for an almost homogeneous emission of light or a satined PMMA microprism for reduced brightness (LRA). Indirect light emission through a diffuser made of satined PMMA. Luminaire equipped with the latest generation of LED boards, small color tolerance MacAdam 3.







Family	Size / Wattage / Lumens				CCT		Finish		Diffuser		Driver		Input voltage	
LILI														
R1	14.5W	>1015lm	recess with trim	dir.	830	3000K	W	white	S	satine	N	non dim	120	120V input
R2	18.5W	>1640lm	recess with trim	dir.	840	4000K	S	**silver	M	***microprism	A	0-10V	277	277V input
R3	27W	>2670lm	recess with trim	dir.	DW	*2700K to 6500K	R	RAL color			C	consult for options		
R4	51W	>5790lm	recess with trim	dir.										
R5	96W	>12177lm	recess with trim	dir.										
R6	172W	>22850lm	recess with trim	dir.										
RT2	18.5W	>1939lm	recess trimless	dir.										
RT3	27W	>3014lm	recess trimless	dir.										
RT4	51W	>6479lm	recess trimless	dir.										
RT5	96W	>13038lm	recess trimless	dir.										
RT6	172W	>24467lm	recess trimless	dir.										
SDI1	38W	>3941lm	surface	dir.-ind.										
SDI2	62W	>7198lm	surface	dir.-ind.										
SDI3	116W	>14479lm	surface	dir.-ind.										
SDI4	191W	>24679lm	surface	dir.-ind.										
PDI1	46W	>4671lm	pendant	dir.-ind.										
PDI2	78W	>8763lm	pendant	dir.-ind.										
PDI3	135W	>16057lm	pendant	dir.-ind.										
PDI4	209W	>26256lm	pendant	dir.-ind.										

Notes: (*) not available for direct-indirect - SDI & PDI
 (**) not available for trimless - RT
 (***) microprism diffuser will reduce wattage & lumen value

example...

Family	Size / Wattage / Lumens	CCT	Finish	Diffuser	Driver	Input voltage
LILI	R1	830	W	S	A	120



R	LxW	RT	LxW	PDI	LxW	SDI	LxW
R1	9.8" dia.	RT2	13.0" dia.	PDI1	16.5" dia.	SDI1	16.5" dia.
R2	13.8" dia.	RT3	16.5" dia.	PDI2	24.4" dia.	SDI2	24.4" dia.
R3	17.3" dia.	RT4	24.4" dia.	PDI3	36.2" dia.	SDI3	36.2" dia.
R4	25.1" dia.	RT5	36.2" dia.	PDI4	48.0" dia.	SDI4	48.0" dia.
R5	37.0" dia.	RT6	48.0" dia.				
R6	48.8" dia.						