



DATE:

CUSTOMER:

PROJECT:

QUANTITY:

PLLMT.52XS *Square 52W / 53W / 112W / 197W LED Metal Trim Surface-Mounted Light*



EXAMPLE:

FAMILY	ITEM#	WATTAGE	LUMENS	CCT	DIFF.	FINISH	DRIVER	CRI	INPUT VOLTAGE
PLLMT	PLLMT.52CS	112W	8400lm	30	P	S	N	80	120



FAMILY	ITEM#	WATTAGE	LUMENS	CCT	DIFFUSER	FINISH	DRIVER	CRI	INPUT VOLTAGE	
PLLMT										
	PLLMT.52AS	52W	3540lm	30	3000K	O Opal	S Silver	N Non-Dim	80 CRI80	120 120V input
	PLLMT.52BS	53W	3540lm	40	4000K	P Prismatic	W White	A 0-10V	90 *CRI90	277 277V input
	PLLMT.52CS	112W	8400lm				C Consult			
	PLLMT.52DS	197W	15000lm							

NOTES	Prestigious surface-mounted with square design for homogenous and sophisticated architectural lighting, no UV and thermal emissions, metal housing, easy ceiling mounting, opal white diffuser made from UV and heat-resistant acrylic glass, 5-pole terminal block, LED converter integrated.	* CRI90 (subject to availability)	WEB LINKS: Product Page